

Fluke 323

The best option for general, grab-and-go troubleshooting needs.

Measurement capability:

- 400 A ac current measurement
- 600 V ac and dc voltage measurement
- True-rms ac voltage and current for accurate measurements on non-linear signals
- Resistance measurement up to 4000 Ω with continuity detection

Features:

- Slim, ergonomic design
- CAT IV 300V/CAT III 600 V safety rating
- Hold button
- Two-year warranty
- Soft carrying case



Technical specifications		
AC current	Range	Accuracy
	400.0 A	2 % ± 5 digits (45 Hz to 65 Hz) 2.5 % ± 5 digits (65 Hz to 400 Hz)
AC voltage	Range	Accuracy
	600.0 V	1.5 % ± 5 digits
DC voltage	Range	Accuracy
	600.0 V	1.0 % ± 5 digits
Resistance	Range	Accuracy
	400.0 Ω 4000 Ω	1.0 % ± 5 digits
Continuity	≤ 70 Ω	
Data hold	Yes	
Category rating	CAT III 600 V, CAT IV 300 V	

Fluke 324

General electrical measurements with temperature and capacitance capabilities.

Measurement capability:

- 400 A ac current measurement
- 600 V ac and dc voltage measurement
- True-rms ac voltage and current for accurate measurements on non-linear signals
- Resistance measurement up to 4000 Ω with continuity detection
- Temperature and capacitance measurement

Features:

- Slim, ergonomic design
- Backlight display
- CAT IV 300V/CAT III 600 V safety rating
- Hold button
- Two-year warranty
- Soft carrying case



Technical specifications		
AC current	Range	Accuracy
	40.00 A 400.0 A	1.5 % ± 5 digits (45 Hz to 400 Hz) <i>Note: Add 2 % for position sensitivity.</i>
AC voltage	Range	Accuracy
	600.0 V	1.5 % ± 5 digits
DC voltage	Range	Accuracy
	600.0 V	1.0 % ± 5 digits
Resistance	Range	Accuracy
	400.0 Ω 4000 Ω	1.0 % ± 5 digits
Continuity	≤ 30 Ω	
Capacitance	100.0 μF to 1000 μF	
Backlight	Yes	
Data hold	Yes	
Contact temperature	-10.0 °C to 400.0 °C (14.0 °F to 752.0 °F)	
Category rating	CAT III 600 V, CAT IV 300 V	

Fluke 325

Big ac/dc features in a small form factor.

Measurement capability:

- 400 A ac and dc current measurement
- 600 V ac and dc voltage measurement
- True-rms ac voltage and current for accurate measurements on non-linear signals
- Resistance measurement up to 40 kΩ with continuity detection
- Temperature and capacitance measurement
- Frequency measurement
- Min/Max functionality

Features:

- Slim, ergonomic design
- Backlight display
- CAT IV 300V/CAT III 600 V safety rating
- Hold button
- Two-year warranty
- Soft carrying case



Technical specifications		
AC current	Range	Accuracy
	40.00 A 400.0 A	2 % ± 5 digits (45 Hz to 65 Hz) 2.5 % ± 5 digits (65 Hz to 400 Hz)
AC voltage	Range	Accuracy
	600.0 V	1.5 % ± 5 digits
DC Current	Range	Accuracy
	40.00 A 400.0 A	2 % ± 5 digits
DC voltage	400.0 A	2 % ± 5 digits
	600.0 V	1.0 % ± 5 digits
Resistance	Range	Accuracy
	400.0 Ω 4000 Ω 40.00 kΩ	1.0 % ± 5 digits
	Continuity	≤ 30 Ω
Capacitance	100.0 μF to 1000 μF	
Frequency	5.0 Hz to 500.0 Hz	
Backlight	Yes	
Data hold	Yes	
Contact temperature	-10.0 °C to 400.0 °C (14.0 °F to 752.0 °F)	
Min/Max	Yes	
Category rating	CAT III 600 V, CAT IV 300 V	

GO TO WORK WITH THE BEST.

Fluke 320 Series True-rms Clamp Meters

